

Go safely back into schools.

Body temperature & facial recognition scanner

Why GoSafe?

- 1. Securely scan in less than one second with on-board Al
- 2. The only scanner with live video assistance for real time entry approval
- 3. Provides access control integration for automatic doors
- 4. Centralized management for multiple scanners, data and attendance
- 5. Free, unlimited help & training







Table Top



made with Qualcom **Technologies**

OneScreen GoSafe can prevent people with elevated temperature or no mask from entering your offices, schools, hospitals & public spaces.



Go safely back into schools.



Connect with doors, gates, peripheral devices & network





SPECIFICATIONS		
Screen		Serial Communication
Size	8.0" IPS LCD screen	Relay Output
Resolution	800x1280	Wiegand
Design	Industrial-grade, waterproof, dustproof & vandal-proof	Upgrade Button
Processor		Access Control
СРИ	Qualcomm Snapdragon Octa-Core Processor	Facial Recognition based Access Con
CPU (Optional)	Rockchip RK3288 Quad-Core	Face Mask Detection based Access Control
System	Android 7.1.2	
Storage	EMMC 8 GB	Elevated Temperature based Access Control
Camera		ID Card based Access Control
Resolution	2 million pixels	Barcode Reader based Access Contro
Туре	Binocular vision wide dynamic camera	Call Receptionist / Security to Grant Access
Aperture	F2.4	Call IT / Screen Skills Guru for Suppor
Focusing Distance	19.6"- 60"	Face Library
White Balance	Auto	•
Photo Flood Light	LED and IR dual photo flood light	Remote Management
Infrared Thermal Imaging Module		Attendance Tracking & Reporting
5 5		User Interface Customization
Temperature Detection	Available	Remote Device Management
Temperature Detection Distance	3.2' (optimal distance 1.6')	Remote Database Management
Temperature Measurement Accuracy	≤ ±0.9 °F	_ Remote Firmware Upgrade
Temperature Measurement Range	50 °F – 107.6 °F	System
Thermal Field of View	89.6 x 89.6 °	Power
Elevated Temperature Alarm	Supported (temperature alarm value can be set)	Operating Temperature
Interfaces		Power Consumption
Network Module	Ethernet (RJ-45) and Wireless (Wi-Fi)	Installation Method
Audio	2.5W / 4R speakers	Product Size
USB	1 USB OTG, 1USB HOST standard A port	What's in the Box
	•	_

Serial Communication	1 RS232 serial port	
Relay Output	1 door open signal output	
Wiegand	1 Wiegand 26/34 output and input	
Upgrade Button	Supports USB boot upgrade button	
Access Control		
	1.1 0 Nr.1 face accomition	
Facial Recognition based Access Control	1:1 & N:1 face recognition	
Face Mask Detection based Access Control	Available	
Elevated Temperature based Access Control	Available	
ID Card based Access Control	Optional IC card, S50, NTAG, CPU, DESfire	
Barcode Reader based Access Control	Optional Barcode, 2D Barcode & QR Code Reader	
Call Receptionist / Security to Grant Access	Available	
Call IT / Screen Skills Guru for Support	Available	
Face Library	Up to 30,000	
Remote Management		
Attendance Tracking & Reporting	Available	
User Interface Customization	Available	
Remote Device Management	Available	
Remote Database Management	Available	
Remote Firmware Upgrade	Available	
System		
Power	DC 12V	
Operating Temperature	0 °F – 140 °F	
Power Consumption	13.5W Max	
Installation Method	Wall Mount, Table Stand & Floor Stand	
Product Size	11.66" x 5.23"x 0.98"	
What's in the Box	OneScreen GoSafe, Power Adapter, User Manual	